



SITE REFERENCE :

COMPANY :

Contact :

Phone :

@ mail :

PRICE REQUEST

FUNCTION

Lighting	Ventilation	Roof Acces	Smoke Evacuation
	<input type="checkbox"/> Manual mechanism <input type="checkbox"/> Electric mechanism		<input type="checkbox"/> Treuil <input type="checkbox"/> Pneumatic <input type="checkbox"/> Electric

TYPES OF INSTALLATION

<input type="checkbox"/> Waterproof roof	<input type="checkbox"/> Dry roof	<input type="checkbox"/> Capping extension
<input type="checkbox"/> Height 310 mm : max. complex 140 mm (ORIGIN' range only) <input type="checkbox"/> Height 360 mm : max. complex 240 mm <input type="checkbox"/> Height 410 mm : max. complex 240 mm <input type="checkbox"/> Other height, please specify : <input type="checkbox"/> Bituminous waterproofing <input type="checkbox"/> PVC waterproofing	<input type="checkbox"/> Dry bin <input type="checkbox"/> Sandwich panel	Profile : RAL : Profile : Thickness : RAL :
		<input type="checkbox"/> 83 mm standard heels <input type="checkbox"/> Other, please specify :

DIMENSIONS + QUANTITIES

Dimensions : Quantities :

CHOICE OF RANGE

<input type="checkbox"/> THERMIK' range	<input type="checkbox"/> ORIGIN' range
<ul style="list-style-type: none"> • 30 mm perimeter upstand insulation • Insulation over the height and return of the upstand • Seals for better airtightness • Wide choice of infills to meet different thermal performance, light transmission and solar factor requirements, from PCA16 to PCA 32+.* • $U_{RC} = 1.2 \text{ W/m}^2.K^*$ • RW sound reduction of 17 to 25 db depending on filling 	<ul style="list-style-type: none"> • Peripheral upstand insulation, thickness 15 mm • Filled with multiwall opal PCA10, double dome, aluminium cover** • $U_g = 2.9 \text{ W/m}^2.K$ • 57% light transmission • Solar factor g to EN410 = 60 %

FILLING

Acoustik Light*
 PCA16*
 PCA32*
 Aluminium cover 40 opaque*
 PCA10**
 Triple dome*
 PCA16+*
 PCA20*
 PCA32+*
 Double dome**
 Insulated aluminium cover**

OPTIONS

GRID	FINISH	ACCESSORIES
<input type="checkbox"/> Fixed 6 mm <input type="checkbox"/> Fixed 16 x 16 mm <input type="checkbox"/> Opening	<input type="checkbox"/> Lacquered upstand RAL 9010 <input type="checkbox"/> Other RAL :	<input type="checkbox"/> Ladder bar <input type="checkbox"/> Holding stock <input type="checkbox"/> Baffles

Others :
 Comments & remarks :

*SKYCLAIR THERMIK' 160 x 160 PCA32+